

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
14 July 2005 (14.07.2005)

PCT

(10) International Publication Number
WO 2005/064120 A1

(51) International Patent Classification⁷: **F01D 5/06**

Carlo [IT/TT]; Piazzale Industria 2, I-53036 Poggibonsi (Siena) (IT).

(21) International Application Number:
PCT/EP2004/014774

(74) Agent: **COPPO, Alessandro**; Ing.Barzano' & Zanardo Milano S.p.A, Via Borgonuovo 10, I-20121 Milano (IT).

(22) International Filing Date:
22 December 2004 (22.12.2004)

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
MI2003A 002607
29 December 2003 (29.12.2003) IT

(71) Applicant (*for all designated States except US*): **NUOVO PIGNONE HOLDING S.p.A.** [IT/TT]; Via F. Matteucci, 2, I-50127 Firenze (IT).


(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **BACCIOTTINI,**

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: DISK OF A DISK ROTOR FOR A GAS TURBINE



(57) Abstract: Disk of a disk rotor for a gas turbine comprising a central portion (22), an intermediate portion (24), an outer portion (28), a series of axial pass-through holes (27) for a series of tie rods and a series of slots (50) for housing a corresponding series of vanes, the central portion (22) comprises a central axial pass-through hole (23), a first collar (30) situated at a first end and a second collar (40) situated at a second end of the central portion (22). The series of holes (27) is positioned in the outer portion (28) of the disk so as to obtain high dynamic characteristics of the rotor and at the same time a sufficient useful life thereof.

WO 2005/064120 A1



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*